

IN THE CLAIMS

Please amend the claims as follows:

Claims 1-10 (Canceled).

Claim 11 (Previously presented): The fluid dispensing container according to claim 13, wherein the at least one low-boiling liquid is at least one selected from the group consisting of isopentane, isohexane, n-pentane, n-hexane, dichloromethane, monochloro propane, 1,1-dichloroethane, 2-chlorobutane, trichloro-fluoromethane CFC 11, trichloro-trifluoro-ethane CFC 113, ethyl ether, methylene-dimethyl ether, dimethoxymethane and acetone.

Claim 12 (Previously presented): The process according to claim 14, wherein the at least one low-boiling liquid is at least one selected from the group consisting of isopentane, isohexane, n-pentane, n-hexane, dichloromethane, monochloro propane, 1,1-dichloroethane, 2-chlorobutane, trichloro-fluoromethane CFC 11, trichloro-trifluoro-ethane CFC 113, ethyl ether, methylene-dimethyl ether, dimethoxymethane and acetone.

Claim 13 (Currently amended): A fluid dispensing container, comprising:

a dispensing pump sealedly mounted on the container;

a fluid product to be dispensed by the dispensing pump; and

at least one low-boiling liquid;

wherein

a per cent by weight of the at least one low-boiling liquid is from 3% to 97% by weight of a total weight of the at least one low-boiling liquid and the fluid product,

the fluid dispensing container does not comprise a pressurized gas,

the at least one low-boiling liquid has a boiling point in the range from 15°C to 85°C
at 760 mm Hg, and

a vapor pressure of the at least one low boiling liquid is less than 1 Kg/cm² at 15°C
and less than 2.8 Kg/cm² at 37.8°C.

Claim 14 (Previously presented): A process for preparing the fluid dispensing
container according to claim 13, comprising:

charging to the container the fluid product to be dispensed by the pump and the at
least one low-boiling liquid;

mounting the dispensing pump on the charged container; and

sealing the dispensing pump on the charged container;

wherein the fluid dispensing container is prepared without any use of pressurized gases.

Claims 15 and 16 (Canceled).

Claim 17 (Currently amended): A fluid dispensing container, consisting essentially
of:

a dispensing pump sealedly mounted on the container; and

a fluid mixture;

wherein

the fluid dispensing container does not comprise a pressurized gas,

the fluid mixture comprises:

active products;

at least one low-boiling liquid having a boiling point in the range from 15°C to 85°C at 760 mm Hg, and a vapor pressure of less than 1 Kg/cm² at 15°C and less than 2.8 Kg/cm² at 37.8°C;

optional additives; and

optional base support products; and

a vapor pressure of the fluid mixture is 2.80 kg/cm² or less at 54.4°C.

Claim 18 (Previously presented): The fluid dispensing container according to claim 17, wherein the at least one low-boiling liquid is at least one selected from the group consisting of isopentane, isohexane, n-pentane, n-hexane, dichloromethane, monochloro propane, 1,1-dichloroethane, 2-chlorobutane, trichloro-fluoromethane CFC 11, trichloro-trifluoro-ethane CFC 113, ethyl ether, methylene-dimethyl ether, dimethoxymethane and acetone.

Claim 19 (Previously presented): The fluid dispensing container according to claim 17, wherein a proportion of the low-boiling liquid is from 3 % to 97% by weight of a total weight of the active products, at least one low-boiling liquid, optional additives and optional base support products.

Claim 20 (Previously presented): A process for preparing the fluid dispensing container according to claim 17, comprising:

charging to the container the fluid product to be dispensed by the pump, optional additives, optional base support products and the at least one low-boiling liquid;

mounting the dispensing pump on the charged container; and

sealing the dispensing pump on the charged container;

wherein the fluid dispensing container is prepared without any use of pressurized gases.

Claim 21 (Currently amended): A fluid dispensing container, consisting of:

a dispensing pump sealedly mounted on the container;

active products;

at least one low-boiling liquid having a boiling point in the range from 15°C to 85°C at 760 mm Hg, and a vapor pressure of less than 1 Kg/cm² at 15°C and less than 2.8 Kg/cm² at 37.8°C;

optional additives; and

optional base support products;

wherein

the fluid dispensing container does not comprise a pressurized gas, and

a vapor pressure of the fluid mixture is 2.80 kg/cm² or less at 54.4°C.

Claim 22 (Previously presented): The fluid dispensing container according to claim 21, wherein the at least one low-boiling liquid is at least one selected from the group consisting of isopentane, isohexane, n-pentane, n-hexane, dichloromethane, monochloro propane, 1,1-dichloroethane, 2-chlorobutane, trichloro-fluoromethane CFC 11, trichloro-trifluoro-ethane CFC 113, ethyl ether, methylene-dimethyl ether, dimethoxymethane and acetone.

Claim 23 (Previously presented): The fluid dispensing container according to claim 21, wherein a proportion of the low-boiling liquid is from 3 % to 97% by weight of a total weight of the active products, at least one low-boiling liquid, optional additives and optional base support products.

Claim 24 (Previously presented): A process for preparing the fluid dispensing container according to claim 21, comprising:

charging to the container the fluid product to be dispensed by the pump, optional additives, optional base support products and the at least one low-boiling liquid;

mounting the dispensing pump on the charged container; and

sealing the dispensing pump on the charged container;

wherein

the at least one low-boiling liquid has a boiling point in the range from 15°C to 85°C at 760 mm Hg, and a vapor pressure of less than 1 Kg/cm² at 15°C and less than 2.8 Kg/cm² at 37.8°C, and

the fluid dispensing container is prepared without any use of pressurized gases.

Claim 25 (Currently amended): A fluid dispensing container, comprising:

a dispensing pump sealedly mounted on the container;

a fluid product to be dispensed by the dispensing pump; and

at least one low-boiling liquid;

wherein

no component having a boiling point less than 15°C at 760 mm Hg is present,

the fluid dispensing container does not comprise a pressurized gas,

a vapor pressure of the at least one low boiling liquid is less than 1 Kg/cm² at 15°C and less than 2.8 Kg/cm² at 37.8°C, and

a vapor pressure within the fluid dispensing container is 2.80 kg/cm² or less at 54.4°C.

Claim 26 (Previously presented): The fluid dispensing container according to claim 25, wherein the at least one low-boiling liquid is at least one selected from the group consisting of isopentane, isohexane, n-pentane, n-hexane, dichloromethane, monochloro propane, 1,1-dichloroethane, 2-chlorobutane, trichloro-fluoromethane CFC 11, trichloro-trifluoro-ethane CFC 113, ethyl ether, methylene-dimethyl ether, dimethoxymethane and acetone.

Claim 27 (Previously presented): The fluid dispensing container according to claim 25, wherein a proportion of the low-boiling liquid is from 3 % to 97% by weight of a total weight of the active products, at least one low-boiling liquid, optional additives and optional base support products.

Claim 28 (Previously presented): A process for preparing the fluid dispensing container according to claim 25, comprising:

charging to the container the fluid product to be dispensed by the pump and the at least one low-boiling liquid;

mounting the dispensing pump on the charged container; and

sealing the dispensing pump on the charged container;

wherein

the fluid dispensing container is prepared without any use of pressurized gases,

no component having a boiling point less than 15°C at 760 mm Hg is charged, and

a vapor pressure of the at least one low boiling liquid is less than 1 Kg/cm² at 15°C and less than 2.8 Kg/cm² at 37.8°C.